TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6807-08)

A Fir 12" dia., for ¼ sec. cor. on S. bdy. sec. 19, I mark ¼ S19 on N. side, from which
A Fir 24" dia., bears N.6½°E., 8 lks. dist. mkd. ¼ S19 BT.
A Fir 10" dia., bears N.30°W., 15 lks. dist. mkd. ¼ S19 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 30, 1968 - C.S. File 54/73-16

Found - 12" D.Fir Corner tree, now rotted stump.
24" D.Fir, now snag, N.6½°E., 5.3 ft., scribe visible.
10" D.Fir, now 8 ft. stob, N.30°W., 6.9 ft. (Rec. 9.9 ft.), scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 19
1968

New BTs- 15" D.Fir N.47°W., 7.8 ft. mkd. ¼ S19 CS BT.
29" D.Fir N.43°E., 46.8 ft. mkd. ¼ S19 CS BT.

Corner lies 68.0 ft. East of ¼ cor. sec. 30.

Fd. OK, Dec. 1985/Feb. 1986 by H. Johnstone - M 100-21