

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 7 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6833)

-----  
A Fir 40" dia. for ¼ sec. cor. on S. bdy. sec. 7, I mark ¼ S.7 on N. side, from which  
    A Fir 36" dia., bears N.41°E., 91 lks. dist. mkd. ¼ S7 BT.  
    A Fir 36" dia., bears N.68°W., 32 lks. dist. mkd. ¼ S7 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - S.A. Bilow; Milo Godfrey, crew - Jan. 30, 1959 - C.S. File 49/86-4

-----  
Found - Orig. 42" now 44" top dead, R.Fir corner tree scribed "¼S7" on N. face.  
    Both orig. BTs now scribed stumps.  
Set Witness Corner 5 ft. East of ¼ cor. mkd. "Wit. Cor. 5' West to South ¼ S7 T30S R2W County Surveyors Office 1959".  
New BTs- 8" R.Fir bears N.3°W., 23.7 ft. scribed W.C. ¼ S7 CS BT.  
    6" R.Fir bears N.47°E., 29.0 ft. scribed W.C. ¼ S7 CS BT.

Fd. OK, Nov. 1968, by DCSO, John Powell - C.S. File 54/73-47A

Fd. and used in BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14515-16)