

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6852-53)

-----  
Set a granite stone 14x8x6 ins., 9½" in the ground for ¼ sec. cor. marked ¼ on N. face, from which  
A Pine 15" dia., bears N.80½°E., 65 lks. dist. mkd. ¼ S6 BT.  
A Pine 15" dia., bears S.36½°E., 127 lks. dist. mkd. ¼ S7 BT.

John H. Markham, Jr. - Wit: J.F. Johnson; B.H. Johnson; Elmar Sutton - Sept. 8, 1952 - C.S. File 41/74-1

-----  
Determined by O.B.T.s:  
A Pine 26" dia., bears N.80°E., 40.0 ft.  
At corner point, found old stone and SET 1" x 30", from which  
A Laurel 8" dia., bears N.3°E., 32.6 ft. mkd. ¼S S6 2880, BT.  
A Pine 26" dia., bears S.86°E., 149.0 ft. mkd. S7 ¼S BT.  
An old fence bears East and West from corner.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-61

-----  
Found - Corner stone and 1" Iron pipe at ¼ corner.  
Orig. 26" Pine N.80°E., 40.0 ft., shows scar.  
26" Pine, now down, S.86°E., 149.0 ft., scribe visible.  
8" Laurel now 16" double, N.3°E., 32.6 ft., bark scribe visible and other faint marks.  
New BT - 25" D.Fir, West 89.3 ft. mkd. ¼ S7 CS BT.  
Reblazed and rescribed:  
16" double Laurel N.3°E., 32.6 ft. mkd. ¼ S6 CS BT

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14520-21)

-----  
The ¼ sec. cor., monumented with the original basalt stone, 14x8x6 ins., firmly set, 6" in the ground, mkd. ¼ on N. face, alongside of which is an iron pipe, 1" dia., firmly set, projecting 8" above the ground, perpetuated and recorded by the County in 1967, from which the remaining original bearing tree:  
A Pine 37" dia., bears N.80½°E., 65 lks. dist. with healed blaze.  
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and trees by the County:

A Fir 25" dia., bears S.89½°W., 136 lks. dist. with scribe marks ¼ S7 CS BT visible on open blaze.

A twin Madrone 19" dia., bears N.1°W., 48 lks. dist. with scribe marks ¼ S6 CS BT visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 2 W

¼  $\frac{S\ 6}{S\ 7}$

1970

Deposit the original stone and reset the iron pipe alongside the iron post.

Fd. BLM BC & BTs by Troy Rambo, July 2002 M140-73