

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 160600

PRIMARY CORNER DESCRIPTION E. 1/16 cor. for secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

John H. Markham, Jr. - Wit: J.F. Johnson; B.H. Johnson; Elmar Sutton - Sept. 8, 1952 - C.S. File 41/74-2

-----  
At midpoint between the North 1/4 cor. Sec. 7 and the NE. cor. Sec. 7, I drove a 3/4" solid steel shift, from which  
A Laurel 10" dia., bears N.85°E., 8.0 ft. mkd. 1/16S BT  
A Sugar Pine 12" dia., bears N.30°W., 15.5 ft. mkd. 1/16S BT.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14520)

-----  
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. E 1/16  $\frac{S\ 6}{S\ 7}$   
1970

from which  
A Pine 8" dia., bears N.23½°E., 15 lks. dist. mkd. E 1/16 S6 BT.  
A Pine 54" dia., bears S.63°E., 58 lks. dist. mkd. E 1/16 S7 BT.

From this point, a point established by Markham in 1952, bears N.46°E., 10½ lks. dist., monumented with an iron rod, 1" dia., firmly set, projecting 5" above ground, from which a tree mkd. by Markham:  
A Pine 20" dia., bears N.31°W., 25 lks. dist., with healed blaze.