

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 178500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17 & 18 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6833)

Set a granite stone 16x12x8 ins., 11" in the ground for cor. of secs. 17 and 18, marked with 4 notches on S. and 5 notches on E. edge, from which
A Fir 12" dia., bears S.38°E., 34 lks. dist. mkd. T30S R2W S17 BT.
A Hemlock 12" dia., bears S.13°W., 51 lks. dist. mkd. T30S R2W S18 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-14

Found - No trace of corner stone.
12" now 17" D.Fir S.38°E., 22.4 ft., shows good scar.
12" Hemlock, now dead, S.13°W., 33.7 ft. scribe visible "S18".
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
S 7
S 18 | S 17
1968
New BTs- 10" Hemlock S.54°W., 12.6 ft. mkd. T30S R2W S18 CS BT.
11" Cedar N.20°E., 24.2 ft. mkd. T30S R2W S7 CS BT.
This corner lies East of creek, about 50 ft.

Fd. and used in BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14514-15)