

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6769)

Set ¼ sec. post, from which
 An Oak 15" dia., bears N.2½°W., 516 lks.
 An Oak 15" dia., bears N.4°E., 455 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6815)

The old ¼ sec. cor. nearly obliterated, no trace is found of the post. Both bearing trees are standing with marks deeply overgrown.
I re-establish the cor. in its original position as follows:
Set a basalt stone 14x10x4 ins., 9½" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
 An Oak 20" dia., bears N.4°E., 455 lks. mkd. ¼ S29 BT.
 An Oak 20" dia., bears N.2½°W., 516 lks. dist. mkd. ¼ S30 BT.
No trees of sufficient sizes more conveniently available.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 31, 1968 - C.S. File 54/73-19

Found - Basalt stone 14x10x4 ins., firmly in ground, mkd. "¼" on West face,
 20" Oak, now down and burnt, N.4°E., 280.3 ft., found scribing.
 20" Oak, now down and burnt, N.2½°W., 340.6 ft., found scribing.

Set Brass cap at cor. mkd: County Surveyors Office
 T 30 S R 2 W
 ¼ S 30 | S 29
 1968

New BTs- 12" S.Pine N.74°W., 54.7 ft. mkd. ¼ S30 CS BT.
 30" S.Pine S.85°E., 208.0 ft. mkd. ¼ S29 CS BT.
Set steel fence post alongside brass cap as corner lies on S. slope in large opening.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1132, surveyed May/June 1983 - (DCSO records Vol. 46 Page(s) 17791-92)

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The ¼ sec. cor., perpetuated and recorded by Powell in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground alongside of which is a basalt stone, 14x10x4 ins., firmly set, 12" in the ground, mkd. ¼ on W. face, with brass cap mkd. in 1968

from which the remains of bearing trees mkd. by Powell:

A sawed Pine stump 25" dia., bears S.86°E., 314 lks. dist., with scribe marks ¼ S29 BT visible on open blaze.

A Pine 24" dia., bears N.73°W., 83 lks. dist., with healed blaze.

and a new bearing tree:

A Pine 16" dia., bears N.34½°E., 173 lks. dist. mkd. ¼ S29 BT.

Fd. OK, Dec. 1995 by H. Johnstone - M 100-21

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2818, surveyed Nov. 2015 - (DCSO records Vol. 58 Page 23488 & Plat T30-2 2017-1)

The ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground (alongside of which is the original basalt stone, 14x10", firmly set, projecting 4". above ground, no marks visible), with brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1968, reported by Rogers and Bishop in 1983

A sawed pine stump, 25" dia., bears S.86°E., 207.2 ft., with scribe marks ¼ S29 BT visible on an open blaze.

and a bearing tree mkd. by Rogers and Bishop

A pine, 32" dia., bears N.34½°E., 114.2 ft., with a healed blaze.

and a new bearing tree

A pine, 10" dia., bears N. 68° W, 42.4 ft., mkd. ¼ S30 BT.
NAD 1983 (2011)

Latitude 42°56'19.10"N. Longitude 122°58'55.30"W.