

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 20 only (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6864)

-----  
Set a quartz stone 15x8x6 ins., 10" in the ground, for closing cor. of secs.19 and 20, marked C C on N. with 5 grooves on E. face, from which  
A Fir 10" dia., bears N.7°E., 30 lks. mkd. T30S R2W S20 BT  
A Fir 12" dia., bears N.50°W., 24 lks. mkd T30S R2W S19 BT

Douglas Co. Surveyors Office - John M Powell & crew - 11/4/1968 - C.S. File 54/73-23A

-----  
Reported as not fd  
Closing cor. fd quarter stone approx. size + on top, no other marks. Should be CC on north face.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - June 29, 1970 - C.S. File 54/73-70

-----  
Found broken quartz stones at closing corner. No trace of BTs. I found these stone approx. a year ago, and since then, Roseburg Lumber has chained from the N. and E. to these points. Everything points to this being the correct position for corners.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 2 W  
CC S 19 | S 20  
S 29  
1970

New BTs- 7" D.Fir N.65°W., 24.0 ft. mkd. T30SR2W S19 CC CS BT  
6" D.Fir S.15°E., 18.7 ft. mkd. S29 CS BT.

No other trees available to the NE.

This corner lies 38.3 ft. East of corner for Secs. 29 & 30.

Fd. OK, Dec. 1985-Feb. 1986 by H. Johnstone - M 100-21

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2818, surveyed Nov. 2015 - (DCSO records Vol. 58 Page 23488 & Plat T30-2 2017-1)

-----  
The closing cor. of secs. 19 & 20 only, on the N. bdy. of section 29, perpetuated by the Douglas County Surveyor's Office in 1970, from original evidence no longer clearly identifiable and is accepted for the cor., monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground (alongside of which are fragments of a quartz stone, size indeterminate, no marks visible), with brass cap mkd.  
continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION C.C. for Secs. 19 & 20 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the BTs mkd. by the Douglas Co. Surveyor's Office  
A fir, 23" dia., bears S.15°E., 18.7 ft., with a healed  
blaze.  
A fir, 10" dia., bears N.65°W., 23.9 ft., with a healed  
blaze.