

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6865)

Set a granite stone 18x12x5 ins., 12" in the ground, for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 36" dia., bears N.33½°E., 40 lks. dist. mkd. ¼ S20 BT.
A Fir 9" dia., bears S.88°W., 13 lks. dist. mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-23

Found - Stone at ¼ cor., approx. size but no marks.
9" now 11" D.Fir, S.88°W., 8.6 ft., shows good scar.
36" now 40" D.Fir N.33½°E., 26.4 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 19 | S 20
1968

All bearing trees OK and tagged.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2818, surveyed Nov. 2015 - (DCSO records Vol. 58 Page 23488 & Plat T30-2 2017-1)

The ¼ sec. cor. of secs. 19 & 20, perpetuated the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
A fir stump, 46" dia., bears N.33½°E., 26.4 ft., with a healed blaze.

A root hole bears S.88°W., 8.6 ft., with fallen fir trunk, 14" dia., lying alongside, with a healed blaze.

and new bearing trees

A fir, 9" dia., bears S.16¾°E., 18.7 ft., mkd. ¼ S20 BT.

A pine, 12" dia., bears S.66¾°W., 8.7 ft., mkd. ¼ S19 BT.

NAD 1983 (2011)

Latitude 42°57'11.64"N.

Longitude 122°58'54.62"W.