

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6861)

Set a slate stone 15x8x6 ins., 10" in the ground, for cor. of secs. 17, 18, 19 and 20, marked with 3 notches on S. and 5 notches on E. edge, from which

- A Fir 12" dia., bears N.42½°E., 10 lks. dist. mkd. T30S R2W S17 BT.
- A Fir 12" dia., bears S.22½°E., 12 lks. dist. mkd. T30S R2W S20 BT.
- A Madrone 15" dia., bears S.34°W., 35 lks. dist. mkd. T30S R2W S19 BT.
- A Fir 10" dia., bears N.41½°W., 50 lks. dist. mkd. T30S R2W S18 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-10

-
- Found - 15x8x6 stone at corner, no notches as described.
12" D.Fir, now down and rotten, N.42½°E., 6.6 ft., found scribing.
12" now 16" D.Fir, S.22½°E., 7.9 ft., shows good scar.
10" D.Fir, now stump, N.41½°W., 33.0 ft., shows good scar.
15" now 23" Laurel S.34°W., 23.1 ft., shows faint scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
S 18 | S 17
S 19 | S 20
1968

- New BTs- 18" D.Fir N.49°E., 15.4 ft. mkd. T30S R2W S17 CS BT.
7" Hemlock N.23°W., 34.4 ft. mkd. T30S R2W S18 CS BT.

This corner lies directly on top of large ridge, running E-W.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2818, surveyed Nov. 2015 - (DCSO records Vol. 58 Page 23488 & Plat T30-2 2017-1)

The cor. of secs. 17, 18, 19, & 20, perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground (alongside of which is the original slate stone, 8x6", firmly set, projecting 6" above ground, no marks visible), with brass cap (properly) mkd:

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which the remains of the original bearing trees
A fir, 24" dia., bears S.22½°E., 7.9 ft., with a healed blaze.
A madrone, 26" dia., bears S.34°W., 23.1 ft., with a healed blaze.
A fir stump, size indeterminate, bears N.41½°W., 33.0 ft., with a rotted out blaze.
and the remaining BT mkd. by the Douglas Co Surveyor's Office
A fir, 24" dia., bears N.47¼°E., 14.4 ft., with a healed blaze.
and new bearing tree
A fir, 11" dia., bears N.43½°W., 16.5 ft., mkd. T30S R2W S18 BT.