

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6860)

-----  
Set a basalt stone 12x10x6 ins., 8" in the ground, for 1/4 sec. cor. mkd. 1/4 on W. face, from which  
A Fir 18" dia., bears S.60°E., 60 lks. dist. mkd. 1/4 S17 BT  
A Cedar 12" dia., bears S.4°W., 21 lks. dist. mkd. 1/4 S18 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-9

-----  
Found - Stone, approx. size, no marks visible at 1/4 corner.  
18" now 30" D.Fir S.60°E., 39.6 ft., shows good scar.  
12" now 26" Cedar S.4°W., 13.9 ft., tree opened before, scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 2 W  
1/4 S 18 | S 17  
1968

Reblazed and rescribed:  
26" Cedar S.4°W., 13.9 ft. mkd. 1/4 S18 CS BT.