

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 8 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6832)

Set a slate stone 16x16x4 ins., 11" in the ground for cor. of secs. 7 and 8, marked with 5 notches on E. edge, from which
A Fir 16" dia., bears N.53°E., 60 lks. dist. mkd. T30S R2W S8 BT.
A Fir 4" dia., bears N.16½°W., 34 lks. dist. mkd. T30S R2W S7 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-15

Found - 16x16x4 stone with 5 notches, out of ground.
16" D.Fir, now stump, N.53°E., 39.6 ft., found scribe.

No trace of NW. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 2 W
S 7 | S 8
S 17
1968

New BTs- 11" Hemlock S.47°E., 29.1 ft. mkd. T30S R2W S17 CS BT.

13" D.Fir N.7°E., 19.0 ft. mkd. T30S R2W S8 CS BT.

10" Hemlock N.16°W., 67.4 ft. mkd. T30S R2W S7 CS BT

Fd. and used in BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14514)

Troy Rambo - For: Seneca Jones Timber Co - 9/2003 - M143-15

Found - 29" DF with a healed face, bears N.8°E., 19.2 ft.
13" WH snag with visible scribes - bears S.47°E., 29.1 ft.

Chopped an "X" at DBH on a 21" GF, bears S.45°W., 28.9 ft.

Did not look for the rec. 10" WH bearing N.16°W., 67.4 ft.

Set - A steel post 1.1 ft. north