TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6850)

Set a granite stone 15x10x8 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 6" dia., bears S.66°E., 24 lks. dist. mkd. ¼ S8 BT.
A Fir 5" dia., bears N.60°W., 5 lks. dist. mkd. ¼ S7 BT.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14518)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: T 30 S R 2 W

¼
S 7 | S 8
1970

from which
A Pine 13" dia., bears N.57°E., 28 lks. mkd. ¼ S8 BT.
A W.Fir 9" dia., bears N.60½°W., 34 lks. mkd. ¼ S7 BT.
From this point, an iron pipe, 1" dia., firmly set, projecting 6" above the ground, bears S.0°06'E., 27 lks.

Troy Rambo - For: Seneca Jones Timber Co -9/ 2003 - M143-15

Found - 14" GF with healed face - bears N.60½°W., 22.4 ft.
15" Pine with healed face - bears N.57°E., 14.8 ft.
Scribed- "¼ S7 BT" on an 8" DF - bears S.36°W., 16.9 ft.
"¼ S8 BT" on a 15" Maple - bears S.36°E., 24.1 ft., bark scribed.