

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6850)

-----  
Set a granite stone 14x8x6 ins., 9½" in the ground, for cor. of secs. 5, 6, 7 and 8, marked with 5 notches on S. and E. edges, from which

- A Madrone 16" dia., bears N.86°E., 30 lks. dist. mkd. T30S R2W S5 BT.
- A Fir 18" dia., bears S.40½°E., 40 lks. dist. mkd. T30S R2W S8 BT.
- A Madrone 8" dia., bears S.23½°W., 38 lks. dist. mkd. T30S R2W S7 BT.
- A Madrone 16" dia., bears N.66°W., 27 lks. dist. mkd. T30S R2W S6 BT.

Survey by John H. Markham, Jr. - Wit: J.F. Johnson; B.H. Johnson; Elmer Sutton - Sept. 8, 1952 - C.S. File 41/74-3

-----  
All four old BTs standing. I remark each tree. At corner point, SET 1" x 30" I.P.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-31

-----  
Found - 1¼" I.Pipe at corner.  
Orig. 16" now 22" Laurel N.86°E., 19.8 ft., face and scribing rotten.  
Orig. 18" now 28" D.Fir S.40½°E., 26.4 ft., shows good scar. Also bark scribe "S8 BT"  
Orig. 8" now 12" Laurel S.23½°W., 25.1 ft., rotten face and scribe.  
Orig. 16" now 24" Laurel N.66°W., 17.8 ft., shows scar.  
New BTs- 5" D.Fir S.16°W., 7.5 ft. mkd. S7 CS BT.  
11" Laurel, North 19.4 ft. mkd. T30S R2W S5 CS BT.  
All trees tagged. Corner lies on top of ridge running N-S.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14519-20)

-----  
The Sec. Cor., perpetuated and recorded by the County in 1963, monumented with an iron pipe, 1¼" dia., firmly set, projecting 14" above the ground, from which the original bearing trees:  
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Madrone 21" dia., bears N.75½°E., 24 lks. dist., with scribe marks T30S R2W S5 visible on open blaze. (Rec. N.86°E., 30 lks.)  
A Fir 33" dia., bears S.43½°E., 42 lks. dist. with scribe marks S8 BT visible on bark. (Rec. S.40½°E., 40 lks.)  
A Madrone 12" dia., bears S.23½°W., 37 lks. dist., no marks remaining on rotted blaze.  
A Madrone 20" dia., bears N.70°W., 28 lks. dist., with scribe mrks S6 BT visible on bark. (Rec. N.66°W.)  
and trees by the County Surveyor:  
A Fir 6" dia., bears S.15°W., 11 lks. dist., with scribe marks C S S7 BT visible on partially healed double blaze.  
A Madrone 12" dia., bears N.1°W., 28 lks. dist., with scribe marks T30S R2W S5 CS BT visible on open blaze.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 30 S R 2 W  
S 6 | S 5  
S 7 | S 8  
1970  
Reset the iron pipe alongside the iron post.