

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6854)

Set a slate stone 14x8x6 ins., 9½" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which
A Madrone 12" dia., bears S.10°E., 27 lks. dist. mkd. ¼ S5 BT.
A Cedar 10" dia., bears S.35°W., 69 lks. dist. mkd. ¼ S6 BT.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14922)

The ¼ sec. cor., monumented with a slate stone, 14x8x6 ins., firmly set, 8" in the ground, with no marks visible, from which the original bearing trees
A Madrone 19" dia., bears S.10°E., 27 lks. dist., with no marks visible on opened and rotted blaze.
A Cedar 31" dia., bears S.32°W., 65 lks. dist., with healed blaze. (Rec. S.35°W., 69 lks.)
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
1/4
S 6 S 5
T 30 S R 2 W
1971
from which a new bearing tree
A Fir 30" dia., bears N.35°E., 16 lks. dist., mkd. ¼ S5 BT.
Deposit corner stone alongside the iron post.