

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 203100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May. 10, 1906 - (DCSO records Vol. 18 Page(s) 7667)

(Intersect N. boundary of the township 2.97 chs. E. of the corner of secs. 31 & 32, T30S R2W)
Set a granite stone 15x15x6 ins., 10" in the ground for closing cor. of secs. 5 & 6 marked CC on S. with 5 grooves on E. and 1 groove on W. face, from which
A Madrone 16" dia., bears S.14°E., 75 lks. dist. mkd. T31S R2W S5 BT.
A Fir 16" dia., bears S.14°W., 20 lks. dist. mkd. T31S R2W S6 BT.

Survey by Loyd R. Moffit - For: U.S. Forest Service - Aug. 1978 - C.S. File 58/176-001B

Found - A granite stone 15" x 15" x 6" marking the closing corner.
A 36" Fir bears S.14°W., 13.2 ft., scar healed over.
24" Madrone, now dead, bears S.14°E., 49.5 ft., scar visible.
Set a 2" Pipe with 3" brass cap stamped: "T30S R2W S32 S6 S5 CC T31S R2W PLS 944 1978".
New BT - 8" Fir bears S.53°E., 21.8 ft. scribed T31S R2W S5 BT.
The original corner stone is buried along side the 2" pipe. The new BT has a brass tag #944 nailed at BT scribe.

Ron Quimby - For: Roseburg Resources Co. - Dec 2014 - M166-27

Found- Brass cap per 1978 U.S.F.S. renewal
45" Fir S.14°W., 13.2' visibly healed "X"
10" Fir S.53°E., 21.8' fully healed visible scar
New BOs- 7" Fir S.82°E., 30.4'
6" Fir S.25°E., 24.5'
Both scribed "T31S R2W S5 BT"