

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 238500

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 17 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6832)

Set a slate stone 12x7x7 ins., 8" in the ground for ¼ sec. cor. on N. bdy. sec. 17, marked ¼ on S. face, from which
A Cedar 18" dia., bears S.49½°E., 36 lks. dist. mkd. ¼ S17 BT.
A Fir 40" dia., bears S.67°W., 30 lks. dist. mkd. ¼ S17 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-46

Found - Stone, approx. 12x7x7, mkd. "¼".
18" now 28" Cedar, S.49½°E., 23.8 ft., shows good scar.
40" now 50" D.Fir S.67°W., 19.8 ft., shows good scar.

All bearing trees OK and tagged.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 17
1968

Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1953, surveyed June/July 2000. (DCSO rec. Vol. 53 page(s) 20679)

Found OK by T. Rambo, Sept. 2003 - M143-15