

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 239200

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 29 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6817-18)

Point midway on S. bdy. sec. 29.
Set a granite stone 12x10x6 ins., 8" in the ground for ¼ sec. cor. on S. bdy., marked ¼ on N. face, from which
A Fir 8" dia., bears N.5°E., 14 lks. dist. mkd. ¼ S29 BT.
A Fir 8" dia., bears N.41°W., 25 lks. dist. mkd. ¼ S29 BT.

A.R. Evans, Deputy Co. Surveyor - April 1951 - C.S. File 44/121 and RM 1-30

Found Granite stone with X and two O.B.T.s chopped out:
8" Fir N.5°E., 14 lks.
8" Fir N.41°W., 25 lks.
Blaze and scribe new BTs:
18" Fir N.45°W., 33.3 ft. mkd. So. ¼ S29 CS BT.
10" Fir N.24°E., 13.1 ft. mkd. So. ¼ S29 CS BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-21

Found - Stone at corner mkd. with X.
Orig. 8" now 14" Fir N.41°W., 16.5 ft., opened, scribe visible.
Orig. 8" now 27" D.Fir N.5°E., 9.2 ft.
10" now 12" D.Fir N.24°E., 13.1 ft., shows good scar.
18" now 18" D.Fir N.56½°W., (Rec. N.45°W.) 33.3 ft., shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 29
1968
All bearing trees OK and tagged.
Corner lies 29.0 ft. W. of ¼ cor. Sec. 32.

Fd. and used in BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1132, surveyed May/June 1983 - (DCSO records Vol. 46 Page(s) 17786-87)