TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 20 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6809)

Set a Fir post, no stones obtainable, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on S. bdy. sec. 20, marked ¼ S20 on N. face, from which

A Madrone 14" dia., bears N.6°E., 40 lks. mkd. ¼ S20 BT.
A Cedar 8" dia., bears N.17°W., 11 lks. mkd. ¼ S20 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - June 29, 1970 - C.S. File 54/73-72

Found - 8" now 14" Cedar N.17°W., 7.3 ft., tree opened, reverse scribe found, "B".
14" now 26" Laurel N.6°E., 26.4 ft., shows scar but rotted out.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 20
1970

New BTs- 36" D.Fir N.10°W., 10.1 ft. mkd. ¼ S20 CS BT.
36" D.Fir N.76°E., 41.9 ft. mkd. ¼ S20 CS BT.

Corner lies 15.1 ft. East of ¼ cor sec 29 only (Rec. 27.7 ft)

Fd. and used in BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1132, surveyed May/June 1983 - (DCSO records Vol. 46 Page(s) 17790)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2818, surveyed Nov. 2015 - (DCSO records Vol. 58 Page 23488 & Plat T30-2 2017-1)

From the North ¼ cor. Section 29, the ¼ sec. cor. of sec. 20 only, bears S.87°26'58" E., 15.16 ft., monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Mensch, reported by Rogers and Bishop in 1983

A sawed, decayed madrone stump, 24" dia., bears N.6°E., 26.4 ft., with no marks visible.
A decayed cedar stump, 18" dia., bears N.17°W., 7.3 ft., with axe marks visible.

and the remains of the bearing trees mkd. by the Douglas Co. Surveyor's Office in 1970, reported by Rogers and Bishop

A broken, decayed fir snag, 35" dia. bears N.80°E. 40.2 ft with scribe marks ¼ S20 CS BT visible on an open blaze.

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 20 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed fir stump, 36" dia., bears N.10½°W., 10.6 ft., with a healed blaze.
and new bearing trees
A fir, 11" dia., bears N.86½°E., 38.1 ft., mkd. ¼ S20 BT.
A fir, 6" dia., bears N.49¼°W., 5.7 ft., mkd. ¼ S20 BT.