

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6862)

Set a quartz stone 12x10x6 ins., 8" in the ground, for 1/4 sec. cor. marked 1/4 on N. face, from which
A Hemlock 15" dia., bears N.64 1/2°W., 13 lks. dist. mkd. 1/4 S17 BT.
A Hemlock 6" dia., bears S.80°E., 59 lks. dist. mkd. 1/4 S20 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - April 15, 1970 - C.S. File 54/73-68

Found - Quartz stone, approx. size, out of ground, no marks. 15" now 20" Hemlock N.64 1/2°W., 8.6 ft., shows good scar.
6" Hemlock, now down, S.80°E., 38.9 ft., opened for scribed "1/4 S20 BT".

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W

1/4 $\frac{S\ 17}{S\ 20}$
New BT - 18" Hemlock S.59°W., 48.7 ft. mkd. 1/4 S20 CS BT.
Reblazed and rescribed:
20" Hemlock N.64 1/2°W., 8.6 ft. mkd. 1/4 S17 CS BT.