

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6832)</p> <p>-----</p> <p>Set a slate stone 12x8x6 ins., 8" in the ground for ¼ sec. cor. on S. bdy. sec. 8, marked ¼ on N. face, from which</p> <p> A Maple 12" dia., bears N.40°E., 44 lks. dist. mkd. ¼ S BT.</p> <p> A Fir 24" dia., bears N.41½°W., 33 lks. dist. mkd. ¼ S BT</p>
<p>Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-47</p> <p>-----</p> <p>Found - Stone at ¼ corner mkd. with X on top. No other marks 24" D.Fir, now stump, N.41½°W., 21.8 ft., opened for scribing "B".</p> <p> 12" Maple, now rotten, N.40°E., 29.0 ft.</p> <p>Set Brass cap at cor. mkd: County Surveyors Office</p> <p style="text-align: center;">T 30 S R 2 W ¼ S 8 1968</p> <p>New BTs- 9" Hemlock N.2°W., 24.6 ft. mkd. ¼ S8 CS BT. 11" Hemlock N.67°W., 21.2 ft. mkd. ¼ S8 CS BT.</p>
<p>Survey by Bruce A. Shaner - For: Longview Fibre Co. - Dec. 1981 - RM 3-55</p> <p>-----</p> <p>Found - 1968 brass cap properly mkd., with a 10" x 8" x7" stone, mkd. with an X, alongside, from which</p> <p> 24" D.Fir stump with the scribe "B" visible, bears N.41½°W., 21.8 ft.</p> <p> 12" Maple, rotted, bears N.40°E., 29.0 ft.</p> <p> 12" Hemlock with scribes visible, bears N.2°W., 24.6 ft.</p> <p> 12" Hemlock, dead and down, no scribes visible, bears N.67°W., 21.2 ft.</p> <p>New BT - 8" W.Fir scribed "¼ S17 BT", bears S.68°W., 21.9 ft.</p>
<p>Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1953, surveyed June/July 2000. (DCSO rec. Vol. 53 page(s) 20678)</p>
<p>Found OK by T. Rambo, Sept. 2003 - M143-15</p>
<p style="text-align: right;">1</p>