

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6851)

Set a Madrone post 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S5 on N. and 8 on S. face, from which
A Fir 16" dia., bears North, 30 lks. dist. mkd. 1/4 S5 BT.
A Fir 18" dia., bears S.89°W., 25 lks. dist. mkd. 1/4 S8 BT.

John H. Markham, Jr. - Wit: E.R. Sutton - March 1, 1955 - C.S. File 41/369

Determined by O.B.T.s:
A 30" Fir bears North, 19.8 ft. I found scribe on this Fir.
At corner point, SET stone, from which
A 16" Laurel bears N.69°W., 29.4 ft. mkd. 1/4 S5 BT.
A 5" Cedar bears S.16°E., 14.0 ft. mkd. 1/4 S BT.
Northwest corner Sec. 8 bears West 2648.0 ft.
This corner lies just on South side of main ridge.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-54

Found - No trace of corner stone.
Orig. 30" now 30" D.Fir, North 19.8 ft., shows good scar.
16" now 18" Laurel N.69°W., 29.4 ft., scribe visible "1/4 S".
5" now 8" Cedar S.16°E., 14.0 ft. scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
1/4 S 5
S 8
1968

All bearing trees OK and tagged.

Troy Rambo - For: Seneca Jones Timber Co -9/ 2003 - M143-15

Found - 32" DF with a healed face - bears North 19.8 ft.
28" Madrone with healed face bears N.69°W., 23.4 ft.
12" Cedar with healed face bears S.18°E., 14.0 ft.
New - Bark scribed "1/4 S8 BT" on a 45" DF, bears S.54°W., 2.1 ft. to a 6" spike @ base of scribes.