

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T31-2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May. 10, 1906 - (DCSO records Vol. 18 Page(s) 7662)

Intersect North bdy. of the township, 1.23 chs. West of the cor. of secs. 4, 5, 32 and 33.

A Fir 36" dia. for closing cor. of secs. 4 and 5, I mark S4 on E.; CC T31S R2W on S.; and S5 on W. side, with 4 notches on E. and 2 notches on W. side, from which

A Fir 12" dia., bears S.33°E., 52 lks. dist. mkd. T31S R2W S4 BT.

A Madrone 20" dia., bears S.1°W., 29 lks. dist. mkd. T31S R2W S5 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-71

Found - 36" now 42" Corner tree, opened West side for scribing "5".
12" now 23" Fir S.33°E., 34.3 ft., shows good scar.
20" now 25" Laurel S.1°W., 19.1 ft., shows good scar
Set brass cap on South side of corner tree, marked:

County Surveyors Office

T 30 S	R
S 32	2
<hr style="width: 50%; margin: 0 auto;"/>	
S 5 S 4	W
T 31 S	
1966	

Reblazed and rescribed:
25" Laurel mkd. "T31S R2W S5 CS BT", S.1°W., 19.1 ft

Survey by William Ruppert, LS #866 - For: U.S. Forest Service Feb. 1979 - C.S. File 58/176-21

Found - 42" D.Fir corner tree.
A 1" I.P. and 1966 DCSO brass cap attached, properly mkd., is next to South side of tree.
24" Madrone S.5½°W., 18.4 ft., scribe visible.
No suitable BT in SE. quadrant. Set 6' steel fence post approx. 2 ft. into the ground and attached BT sign. Painted top of post red. Post bears S.70 3/4°E., 17.8 ft. from corner tree.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T31-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Survey by Loyd R. Moffit, LS #944 - For: U.S. Forest Service
Oct. 1986 - C.S. File 62/30-11

Found - 1966 DCSO 2½" brass cap on a 1" iron pipe, is on
South side of corner tree.
A 42" Fir corner tree with scribe visible.
Found remains of Fir BT, S.70 ¾°E., 17.8 ft.
(steel fence post with signs stand where tree
was.)
24" Madrone which bears S.05½°W., 18.7 ft., scribe
visible.
New BT - 8" Fir which bears S.25°E., 20.1 ft. mkd. T31S R2W
S4 BT with an LS 944 brass washer nailed to BT
scribe.

Fd Ok by Ken Hoffine 7/1999 M 133-1

BLM dependent resurvey by Timothy J. Moore, Cadastral
Surveyor and Robert H. Browning, Surveying Technician, under
Group No. 2071, surveyed April/May 2004 - (DCSO records Vol.
55 Page(s) 21378-9)

The closing cor. of secs. 4 & 5, on the N. bdy. of the Tp.,
perpetuated by Powell, in 1966, further perpetuated by
Ruppert, in 1979, further perpetuated by Moffit, in 1986.
This cor. is accepted as marking the township boundary,
monumented with the remains of the original cor. tree, a
sawed fir stump, 44" dia., with healed blazes on S, E, & W
faces, (alongside of which is an iron pipe, 1¼" dia.,
loosely set, projecting 18" above the ground and attach to
the south side of the corner tree stump, with brass cap
mkd. COUNTY SURVEYORS OFFICE T30S S32 S5 S4 T31S 1966, from
which the remains of original bearing trees
A roothole, bears S.33°E., 34.3 ft., alongside of which
is the fir trunk, size indeterminate, with no marks
visible.
A madrone, 27" dia., bears S.1°W., 19.1 ft., with a
healed double blaze.
and an accessory set by Ruppert
A steel fence post, bears S.72°E., 18.9 ft
and a bearing tree mkd. by Moffit
A fir, 13" dia., bears S.25¼°E., 20.0 ft., with a healed
blaze.
and new accessory

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 279100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A stainless steel post, 28" long, 2½" dia., set 24" in the ground for a reference monument, bears S.43°13'21"W., 12.23 ft. with brass cap mkd. T31S R2W RM S5 12.23 FT TO COR 2004 and an arrow pointing to the corner.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description
Deposit a magnet in a white plastic case at the base of the stainless steel post
Corner is located 6.0 ft. west of a spur which slopes N.