

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 279700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6219-20)

Set a granite stone 18x7x7 ins., 12" in the ground for cor. of secs. 32 and 33, marked with 4 notches on E. and 2 notches on W. edge; from which
A Fir 36" dia., bears N.21°15'E., 51 lks. dist., mkd. T29S R2W S33 BT.
A Balsam Fir 15" dia., bears N.64°45'W., 56 lks. dist., mkd. T29S R2W S32 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-44

Found - Stone approx. size, 4 notches E., 2 notches W.
36" now 39" D.Fir N.21°E., 33.7 ft., shows good scar
15" now 19" Fir N.64 3/4°W., 37.0 ft., shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R2W 1/4 S32|S33
T 30 S 1968
New BT - 14" Cedar S.20°E., 28.6 ft. mkd. T30S R2W S5 CS BT
This corner lies 62.7 ft. West of sec. cor. for 4 & 5, T30-2

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22648)

The cor. of secs. 32 & 33 only, on the N. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 1/2" dia. firmly set, projecting 15" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Strickler in 1917
A fir, 46" dia., bears N.21 1/4°E., 33.7 ft., with a healed blaze.
A fir snag, 23" dia., bears N.63 3/4°W., 37.0 ft., with a healed blaze.
and a BT mkd. by the Douglas County Surveyor's Office
A cedar, 16" dia., bears S.10 1/2°E., 28.2 ft., with a healed blaze.
and a new bearing tree
A fir, 8" dia., bears N.75 1/4°W., 33.9 ft., mkd. T29S R2W S32 BT.
Corner is located on a NE. slope.
NAD 1983 (CORS)
Latitude: 43°00'17.00"N Longitude: 122°57'42.61" W