

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6766)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Laurel 12" dia., bears N.60°E., 10 lks. A Fir 30" dia., bears S.10°W., 20 lks.</p>
<p>GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6818 and 6819)</p> <p>-----</p> <p>(Page 6818) The ¼ sec. cor. is not found after careful search. (Page 6819) Set a granite stone 15x12x10 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which A Fir 8" dia., bears S.67½°E., 12 lks. dist. mkd. ¼ S33 BT. A Madrone 15" dia., bears N.76°W., 19 lks. dist. mkd. ¼ S32 BT.</p>
<p>Bruce A. Shaner - For: Umpqua National Forest - Oct. 1967 - C.S. File 55/51 and RM 1-62</p> <p>-----</p> <p>Found - Granite stone 15x12x10"., 10" in ground, mkd. "¼" from which a: 16" D.Fir BT with old face, bears S.53°E., 7.9 ft. 15" Madrone BT now blown down but with scribe visible, bears N.76°W., 12.5 ft. Scribed- 40" D.Fir BT, scribed ¼S S32 BT, S.86°W., 35.0 ft.</p>
<p>Survey by William Ruppert, LS #866 - For: U.S. Forest Service April 1979 - M 70-61</p> <p>-----</p> <p>Found - Stone set firmly in ground with X on top and ¼ on West face. 42" D.Fir S.85°13'W., 35.4 ft. "¼ S32 BT" visible. 22" D.Fir S.64°28'E., 8.0 ft., good scar. 20" Madrone windfall N.76°W., 12.5 ft. Set 2" x 30" galv. Iron pipe with 2½" brass cap. Buried the stone with the pipe.</p>
<p>Mark Smalley, L.S. #2354 - For: Roseburg Resources Co. - April 1995 - M 121-77</p> <p>-----</p> <p>Found - 1979 Brass cap mkd: PLS 866</p> <p>(Cont. Next Page)</p>

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

20" madrone N.76°W., 12.5', down & rotten.  
24" fir, S.64°E., 8.0', healed.  
46" fir, S.85°W., 35.4', healed.  
New BTs- 6" fir, N.5°E., 26.9', scribed "¼ S BT"  
10" fir, S.36°W., 14.8', scribed "¼ S BT"

Fd Ok by Ken Hoffine 7/1999 M 133-1