

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6766-67)

- 
- A Fir 6" dia., cor. secs. 28, 29, 32 and 33, from which
  - A Fir 12" dia., bears S.50°W., 7 lks.
  - A Fir 10" dia., bears S.15°E., 5 lks.
  - A Fir 12" dia., bears N.50°E., 118 lks.
  - An Oak 12" dia., bears N.15°W., 28 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6816-17)

-----

The cor. of secs. 28,29, 32 and 33, partially obliterated. Two of the BTs are not found. The other BTs and the cor. are deeply overgrown. At the Sec. cor., I re-establish the cor. in its original position as follows:  
The original corner tree, A Fir 15" dia., I mark T30S S28 on NE.; R2W S33 on SE.; S32 on SW.; and S29 on NW. sides, with 1 notch on S. and 4 notches on E. side, from which

- A Fir 36" dia., bears N.33°E., 88 lks. dist., mkd. T30S R2W S28 BT.
- A Fir 15" dia., bears S.87°E., 7 lks. dist. mkd. T30S R2W S33 BT.
- A Fir 16" dia., bears S.88°W., 90 lks. dist. mkd. T30S R2W S32 BT.
- A Fir 18" dia., bears N.61°W., 71 lks. dist., mkd. T30S R2W S29 BT.

H.L. Eppstein - Wit: W.L. Dolan; Fred Tolle; Stanley Roach - June 9, 1926 - Only record found, "Old" corner book, page 140

-----

Set 4" x 4" x 30" Laurel post from three old BTs.  
Marked BTs as follows:

- A 36" Fir N.31°E., 81 lks.
- A 20" Fir N.65°30'W., 72 lks.
- A 24" Fir S.50°W., 7 lks. (Old BT)
- A 30" Fir S.72°E., 16 lks.

A.R. Evans, Deputy - Irving and Clinton - May 1951 - C.S. File 44/121

-----

Location was determined by four O.B.T.s in good shape:

- 36" Fir N.31°E., 81 lks.
- 20" Fir N.65½°W., 72 lks.

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" Fir S.50°W., 7 lks.  
30" Fir S.72°E., 16 lks.  
A cross was marked on an 18" x 18" granite stone in place for the exact location of the corner and an 1¼" Iron pipe was driven alongside.

---

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-67  
-----  
Found - 18"x18" stone and 1½" I.Pipe at corner.  
Orig. 36" D.Fir now stump, N.31°E., 53.5 ft.  
Orig. 20" D.Fir now stump, N.65½°W., 47.5 ft., opened for scribing.  
Orig. 24" D.Fir now snag, S.50°W., 4.6 ft., shows good scar.  
Orig. 30" D.Fir now down, S.72°E., 10.6 ft., shows good scar.  
No trees available for bearing trees in burnt area.  
Set two 6 ft. steel fence posts, East 8.0 ft. and 16.5 ft.  
Corner lies on top of small ridge about 15.0 ft. East of old down fence line, running N. and S.

---

Fd. OK, Feb. 1994 by Beckley - M 121-55

---

2