

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300338

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 21 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6859)

Set a slate stone 15x12x6 ins., 10" in the ground, for 1/4 sec. cor. on W. bdy. sec. 21, marked 1/4 on E. face, from which
A Fir 48" dia., bears N.50°E., 23 lks. dist. mkd. 1/4 S21 BT
A Fir 16" dia., bears S.78°E., 15 lks. dist. mkd. 1/4 S21 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - June 30, 1970 - C.S. File 54/73-74

Found - 15x12x6" stone, firmly in ground, with chisel marks on East face.
48" now 58" D.Fir N.50°E., 15.2 ft., shows good scar
16" now 20" D.Fir S.78°E., 9.9 ft., shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
1/4 | S 21
1970

All bearing trees OK and tagged.

Corner lost due to slide. Visited July 21, 1983 by DCSO, L. Monrean - C.S. File 62/9-20

Looked for not found, March 22, 1991 - C.S. File 64/13-13