

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 20 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6859)

Set a slate stone 16x12x5 ins., 11" in the ground, for ¼ sec. cor. on E. bdy. sec. 20, marked ¼ on W. face, from which
A Maple 6" dia., bears S.63°W., 10 lks. dist. mkd. ¼ S20 BT.
A Fir 72" dia., bears N.62°W., 72 lks. dist. mkd. ¼ S20 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - June 30, 1970 - C.S. File 54/73-73

Found - No trace of corner stone nor SW. bearing tree.
72" now 76" D.Fir N.62°W., 47.5 ft., opened for scribe "B".
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 20 |
1970
New BT - 6" D.Fir N.14°W., 51.1 ft. mkd. "¼ S20 CS BT".

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - Wit: J. M. Powell - July 21, 1983 - C.S. File 62/9-19

Found - 1" Iron pipe with attached 1970 DCSO brass cap, protruding from mound of stone approx. 18".
Orig. 72" Fir, now 76" dia. with well healed blaze, bears N.62°W., 46.3 ft. (Rec. 47.5 ft.)
6" D.Fir now 10" with well healed double blaze, bears N.14°W., 51.1 ft.
No new monument set. Mound stone around found monument.
New BT - A 7" Hemlock double blazed and scribed "¼ S20 CS BT" bears n.40°W., 27.4 ft.
Corner is approx. 33 ft. South of creek, course East.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, Terrie Franssen, crew - March 22, 1991 - C.S. File 64/13-12

Found - 2½" 1970 DCSO brass cap on a 1¼" O.D. x 36" long Iron pipe tipped over East of plumb, 1 ft. below ground.
72" now 60" dia., 7 ft. high charred D.Fir stump with blazes, bears N.62°W., 47.5 ft. (Orig.)
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 20 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

6" now 12" dia., 2½ ft. tall D.Fir stump tipped on face, out of position, near record brg. & dist. (N.14°W., 51.1 ft.) is in a slide.

7" now 9" dia., 5 ft. high Hemlock stump, scribing visible on an unhealed blaze "¼ S20 CS" bears N.40°W., 27.4 ft.

DCSO BC/IP returned to plumb, now protrudes 8" above ground. Corner is in a rock slide.

New BTs- 12" dia., 12 ft. high pistol butt Maple stump with a PK nail set through BT tag on South side of stump, 2 ft. above ground, PK nail bears S.40°W., 3.4 ft.

12" dia., 3 ft. high Maple stump with a boat spike stamped "BO 1" set through BT tag near center of stump. Spike bears N.2°E., 65.1 ft.