

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16 and 21 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6857)

Set a granite stone 16x10x8 ins., 11" in the ground for closing cor. of secs. 16 and 21, marked C C on E. with 3 grooves on N. and S. faces, from which
A Fir 30" dia., bears N.25°E., 38 lks. dist. mkd. T30S R2W S16 BT.
A Fir 24" dia., bears S.72°E., 19 lks. dist. mkd. T30S R2W S21 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-62

Found - Stone 16x10x8, set firmly with C C on East face.
30" now 37" D.Fir N.25°E., 25.1 ft., shows good scar
24" now 29" D.Fir S.72°E., 12.5 ft., shows good scar
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
S 20 | S 16 C.C.
S 21
1968

All bearing trees OK and tagged.
This cor. lies 100 ft. South of Sec. cor. for 17 & 20.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Sept. 20, 1984 - C.S. File 58/296-5

Found - 1968 DCSO brass cap and iron pipe, and stone.
36" Fir N.25°E., 25.1 ft., snag and rotten.
32" Fir S.72°E., 12.5 ft., snag and rotten.
New BTs- W.Fir 12", N.31°E., 37.8 ft. scribed with sec. & BT
Cedar 6", S.24°E., 38.0 ft. scribed with sec. and BT

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, Terrie Franssen, crew - March 22, 1991 - C.S. File 64/13-10

Found - 2½" 1968 DCSO brass cap on a 1¼" O.D. Iron pipe, protruding 14" above ground.
Orig. 16"x10"x8" stone with faint marks "CC" on South face, found loose on top of ground, along North side of brass cap.
30" now 32" dia., 6 ft. high burnt and rotted D.Fir snag, no blazes or scribing visible, bears N.21°E., 25.1 ft. (Rec. N.25°E., 25.1 ft.) Orig.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16 and 21 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

24" now 30" dia., 4 ft. high burnt and rotted D.Fir stump with a healed blaze, bears S.72°E., 12.5 ft. (agrees w/rec) Orig. BT.

12" now 13" dia. W.Fir with a partially healed single blaze scribing visible "S16 BT" bears N.29°E., 37.8 ft. (Rec. N.31°E., 37.8 ft.)

6" now 6" dia. 18" high burnt Cedar stump with scribe marks "BT" visible on burnt blaze, bears S.24°E., 28.0 ft. (agrees w/rec.)

New Accessories:

8" dia. I.Cedar, double blazed and scribed "T30S R2W S16 CC CS BT" bears N.72°E., 24.8 ft.

32" dia., 2 ft. high D.Fir stump with an 8" long boat spike set through BT tag near center of stump, boat spike is stamped "BO 1". Spike bears S.84°E., 15.1 ft.

36" dia., 3 ft. high D.Fir stump with an 8" long boat spike set near center of stump, spike stamped "BO 2". Spike bears S.31°E., 20.4 ft.

DCSO BC/IP for SW cor. sec.17 bears North 100 ft.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1953, surveyed June/July 2000. (DCSO rec. Vol. 53 page(s) 20673-4)

The cor. of secs. 16 & 21 only, perpetuated by Powell, in 1968, further perpetuated by Johnstone, in 1984, and further perpetuated by Smith, in 1991, monumented with an iron pipe, 1½" dia., firmly set, projecting 8" above ground (the orig. granite stone, 16X10X8", with marks CC visible on a face, lying loose along the north side), with brass cap (properly) mkd.

from which the remains of the original bearing tree

A sawed, burnt, and decayed fir stump, dia. indeterminate, bears N.21¼°E., 25.8 ft., no marks visible, (Record, N.25°E., 25.1 ft.)

and the remains of bearing trees mkd. by Smith

A cedar, 10" dia., bears N.72½°E., 24.3 ft., with a healed double blaze.

A sawed fir stump, 39" dia., bears S.84°E., 15.1 ft., no marks visible, and a spike driven near the center, top stamped BO1.

A sawed fir stump, 36" dia., bears S.30½°E., 20.5 ft., no marks visible, and a spike driven near the center, top stamped BO2.

and a new bearing tree

A fir, 6" dia., bears N.36¾°E., 5.9 ft., mkd. X BT.