

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17 and 20 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6856)

Set a quartz stone 15x8x8 ins., 10" in the ground, for cor. of secs. 17 and 20, marked with 3 notches on S. edge, from which

A Fir 20" dia., bears S.54°W., 24 lks. dist. mkd. T30S R2W S20 BT.

A Fir 40" dia., bears N.35°W., 51 lks. dist. mkd. T30S R2W S17 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 5, 1968 - C.S. File 54/73-63

Found - No trace of stone.

20" now 26" D.Fir S.54°W., 15.8 ft., shows good scar, we open and find scribe.

40" now 48" D.Fir N.35°W., 33.7 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T	30	S	R	2	W
	S	17		S	16
	S	20			
				1968	

All bearing trees OK and tagged.

This corner lies 100 ft. North of C C of Secs. 16 & 21.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Sept. 20, 1984 - C.S. File 58/296-4

Found - 1968 County brass cap and iron pipe. Good.

45" Fir N.35°W., 33.7 ft. Good.

24" Fir S.54°W., 15.8 ft., snag and rotten.

New BT - W.Fir 6", S.35°W., 25.2 ft., scribed with section and BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - March 22, 1991 - C.S. File 64/13-11

Found - 2½" dia. 1968 DCSO brass cap on a 1¼" O.D. Iron pipe, protrudes 11" above ground.

20" now 26" dia., 6 ft. high D.Fir stump with a previously opened bark, scribing visible "T" bears S.54°W., 15.8 ft. Orig. BT, agrees rec.

40" now 44" dia. D.Fir with a fully healed single blaze, bears N.35°W., 33.7 ft. Orig. BT, agrees w/record.

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17 & 20 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

6" now 6" dia. 5 ft. high Fir stump with an unhealed single blaze, scribing visible "S20 SC BT" bears S.35°W., 25.2 ft. (agrees w/record)
New BTs- 15" dia. W.Fir double blazed and scribed "T30S R2W S17 CS BT" bears N.78°W., 20.3 ft.
4" dia. W.Fir double blazed and scribed "X BT" bears S.75½°W., 22.8 ft.
DCSO BC/IP for C C S16 bears South 100 ft.

FD. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1953, surveyed June/July 2000. (DCSO rec. Vol. 53 page(s) 20674)