

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300438

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 16 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6858)

I establish the ¼ sec. cor. on W. bdy. sec. 16 as follows:
A Fir 10" dia. for ¼ sec. cor. on W. bdy. sec. 16, I mark ¼ S16 on E. side, from which
 A Cedar 10" dia., bears N.81°E., 70 lks. dist. mkd. ¼ S16 BT.
 A Maple 12" dia., bears S.37°E., 34 lks. dist. mkd. ¼ S16 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-13

Found - No trace of Corner tree nor SE. BT.
 10" Cedar, now dead, N.81°E., 46.2 ft., opened for scribe "S16".

Set Brass cap at cor. mkd: County Surveyors Office
 T 30 S R 2 W
 ¼ | S 16
 1968

New BTs- 12" Cedar S.66°E., 176.3 ft. mkd. ¼ S16 CS BT.
 8" Cedar S.34°E., 140.3 ft. mkd. ¼ S16 CS BT.

FD. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1953, surveyed June/July 2000. (DCSO rec. Vol. 53 page(s) 20675)