

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8 & 9 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6831)

Set a basalt stone 16x8x8 ins., 11" in the ground for cor. of secs. 8 and 9, marked with 4 notches on E. edge, from which
A Fir 7" dia., bears N.24°E., 20 lks. dist. mkd. T30S R2W S9 BT.
A Fir 7" dia., bears N.78°W., 7 lks. dist. mkd. T30S R2W S8 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-5

Found - No trace of corner stone or NW. bearing tree.
7" Fir, down and burnt, N.24°E., 13.2 ft., opened for scribe "T" and other marks.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 2 W

S 8 | S 9

S 16

1968

New BTs- 10" D.Fir N.56°W., 65.0 ft. mkd. T30S R2W S8 CS BT
8" D.Fir S.25°W., 17.0 ft. mkd. T30S R2W S16 CS BT.
No other trees available.

Corner lies 115.5 ft. East of cor. to secs. 16 & 17.

Survey by Bruce A. Shaner - For: Longview Fibre Co. - Dec. 1981 - RM 3-55

Found - 1968 DCSO brass cap, properly mkd.
7" D.Fir, down and burnt, bears N.24°E., 13.2 ft. Orig., is now gone.
14" D.Fir with healed over face, bears N.56°W., 65.0 ft.
12" D.Fir with healed over face, bears S.25°W., 18.2 ft. (Rec. 17.0 ft.)
New BT - 8" D.Fir, scribed "T30S R2W S9 BT" bears N.65°E., 21.4 ft.

Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1953, surveyed June/July 2000. (DCSO rec. Vol. 53 page(s) 20677)

Found OK by T. Rambo, Sept. 2003 - M143-15

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8 & 9 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2190, Surveyed June 2008 - (DCSO records Vol. 56 Page(s) 21962)

The cor. of secs. 8 and 9 only, remonumented by Douglas County Surveyors Office in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.

from which BTs mkd. by Douglas County Surveyors Office, reported by Moore and Browning

A fir, 25" dia., bears N.64¾°E., 20.9 ft., with a healed blaze.

A fir, 27" dia., bears N.56°W., 64.4 ft., with a healed blaze.

and a bearing tree mkd. by Shaner in 1981-82, reported by Moore and Browning

A fir, 26" dia., bears S.24½°W., 18.3 ft., with a healed blaze.

Corner is located on a W. slope, 1 ft. South of a wooden fence post at the corner of barbed-wire fence lines extending N. and E.

From the corner N.0°05'00"E., at:

265 ft. dist., a dirt road intersection, 14 ft. wide, with roads extending N.45°W., N.80°W., and S.45°E.

From the corner S.89°42'10"E., at:

80 ft. dist., a gravel road, 14 ft. wide, bears N.10°E. and S.10°W.