

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6846)

Set a slate stone 12x10x5 ins., 8" in the ground, for 1/4 sec. cor., marked 1/4 on W. face, from which

A Fir 24" dia., bears N.6 1/2°E., 44 lks. mkd. 1/4 S9 BT.

A Maple 12" dia., bears S.53 1/2°W., 9 lks. mkd. 1/4 S8 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-55

Found - Stone, approx. size, marked "1/4".
12" now 16" maple S.53 1/2°W., 5.9 ft., found scribing "8", tree opened earlier.

No trace of NE. bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 2 W

1/4 S 8 | S 9

1968

New BTs- 8" D.Fir N.60°E., 54.0 ft. mkd. 1/4 S9 CS BT.

8" R.Fir N.65°W., 32.7 ft. mkd. 1/4 S8 CS BT.

Survey by Bruce A. Shaner - For: Longview Fibre Co. - Dec. 1981 - RM 3-55

Found - 1968 brass cap, properly mkd. with 10" x 9" x 5" stone laying alongside, no marks on stone.

16" split Maple with no scribes visible, bears S.53 1/2°W., 4.2 ft. (Rec. 5.9 ft.)

8" D.Fir stump with tin covering, and no scribes visible, bears N.55°E., 54.0 ft. (Rec. N.60°E.)

12" W.Fir, dead and down, with scribes visible, bears N.61°W., 32.7 ft. (Rec. N.65°W.)

New BTs- 14" D.Fir scribed "1/4 S8 BT" bears S.76°W., 63.3 ft.

16" D.Fir scribed "1/4 S9 BT" bears S.40°E., 48.9 ft.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - Randall Smith and Stephen Flause, crew - Aug. 13, 1984 - C.S. File 62/21-42

Found - Firmly set and 8" below surface, the iron pipe with properly mkd. DCSO brass cap.

The original stone, measures approx. 11"x8 1/2"x5". The center of the stone bears N.44°E., 0.5 ft. from the brass cap. The faint mark "1/4" was located on the bottom of the stone as found. (Photo in C.S. File)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 12" Maple, double trunk with northerly trunk split and dead, no scribing found, bears S.53½°W., 5.9 ft. to center of root crown. Shaner in 1981 calls 4.2 ft. dist. which checks well to center of trunk at apparent ground level (slide activity has covered lower portion of the trunk)

Orig. Fir BT, not found.

8" Fir now an 11" Fir stump with tin roof, partially healed blaze, bears N.55°E., 54.0 ft.

12" W.Fir, dead and down.

14" now 20" D.Fir with scribing "¼ S8 BT" visible in partially healed blaze, bears S.78½°W., 63.3 ft. (Rec. S.76°W.)

16" now 22" D.Fir with scribing "¼ S9 BT" visible in partially healed blaze, bears S.40°E., 48.9 ft.

No new monument set. Area excavated to expose brass cap.

New BTs- 17" D.Fir, double blazed and scribed "¼ S8 CS BT", bears S.36½°W., 14.5 ft.

15" Maple, double blazed and scribed "¼ S8 CS BT", bears N.69°W., 30.7 ft. (Lower blaze bears N.67°W.)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2190, Surveyed June 2008 - (DCSO records Vol. 56 Page(s) 21963)

The ¼ sec. cor. of sec. 9 only, perpetuated by Douglas County Surveyors Office in 1968, subsequently perpetuated by Shaner in 1980, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A roothole bears N.32°E., 22.4 ft., with an uprooted, sawed fir stump, 36" dia., lying alongside, with no marks visible.

A roothole bears N.84°W., 54.1 ft., with a fallen fir snag, size indeterminate, lying alongside, with a healed blaze.

and a bearing tree mkd. by Douglas County Surveyors Office

A cedar 26" dia bears N.84½°W. 17.9 ft with a healed blaze and a bearing tree mkd. by Shaner

A cedar, 11" dia bears N.19°W. 32.0 ft with a healed blaze

Corner is located on a broken NE. slope, in a barbed-wire fence line, fence bears E. and W.

From this corner, the 1/4 sec. cor. of sec. 16 only bears S. 89° 28' 17" W., 208.22 ft. dist., described on page 21964.