

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6847)

Set a granite stone 15x10x5 ins., 10" in the ground for cor. of secs. 4, 5, 8 and 9, marked with 5 notches on S. and 4 notches on E. edge, from which
A Fir 48" dia., bears N.31°E., 34 lks. dist. mkd. T30S R2W S4 BT.
A Maple 6" dia., bears S.60°E., 58 lks. dist. mkd. T30S R2W S9 BT.
A Fir 36" dia., bears S.63°W., 55 lks. dist. mkd. T30S R2W S8 BT.
A Fir 40" dia., bears N.8°W., 41 lks. dist. mkd. T30S R2W S5 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-56

Found - Stone 15x10x5, firmly set at corner, mkd. with 5 notches on S. and 4 notches on E.
48" D.Fir, now stob, N.31°E., 22.4 ft., shows good scar, partly opened, faint burnt scribe marks.
6" now 16" Maple S.60°E., 38.3 ft., shows scar.
No trace of SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
S 5 | S 4
S 8 | S 9
1968

New BTs- 10" D.Fir N.57°E., 16.8 ft. mkd. T30S R2W S4 CS BT.
9" D.Fir N.7°W., 46.7 ft. mkd. T30S R2W S5 CS BT.
14" D.Fir S.69°W., 123.5 ft. mkd. T30S R2W S8 CS BT.

Ron Quimby - Crew: N. Fromdahl & R Heichel- 9/2018 - C.S. File 65/102-1

Found - DCSO brass cap (properly marked)
48" Fir snag N.31°E., 22.4 ft. open, faint scribe.
20" Fir N.57°E., 16.8 ft. faint scar.
18" Fir N.7°W., 46.7 ft faint scar.
22" Fir S.69°W., 123.5 ft. faint scar.
New - 18" S.73°E., 16.0 ft. scribed T30S R2W S9 BT.
Note - Compass decl. 15½°E.