

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 16 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6855)

-----  
Set a basalt stone 16x10x8 ins., 11" in the ground, for ¼ sec. cor. on N. bdy. sec. 16, marked ¼ on S. face, from which  
A Cedar 9" dia., bears S.56½°E., 20 lks. mkd. ¼ S16 BT.  
A Fir 10" dia., bears S.9°W., 18 lks. mkd. ¼ S16 BT.

V.R. Tracey, DCSO - Oct. 1968 - C.S. File 54/73-1A

-----  
"Chaining from the S¼ S9 we find no trace of cor. stone or BTs called for due to cat logging."

Survey by Bruce A. Shaner, LS #430 - Longview Fibre Co. - Aug. 1980 - RM 3-35

-----  
Found - Orig. 16" x 10" x 6" basalt stone mkd. "¼".  
Orig. 12" D.Fir bears S.9°W., 11.9 ft. down and rotted with partial scribes visible.  
Set brass cap mkd. "T30S R2W W.M. 1/4S S16 only RLS 430 1980"  
New BTs- 8" D.Fir bears S.8°W., 25.1 ft. scribed ¼ S16 BT.  
19" Cedar bears S.53°E., 37.9 ft. scribed ¼ S16 BT.  
I reset stone alongside brass cap.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2190, Surveyed June 2008 - (DCSO records Vol. 56 Page(s) 21964)

-----  
The ¼ sec. cor. of sec. 16 only, perpetuated by Shaner in 1980, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, in a collar of stone (alongside of which is the original basalt stone, 16x10x6", firmly set, projecting 4" above ground, mkd. ¼ on S. face), with brass cap (properly) mkd.

from which the remains of an original bearing tree

A roothole bears S.9°W., 11.9 ft.

and bearing trees mkd. by Shaner

A cedar, 27" dia., bears S.53¼°E., 38.0 ft., with a healed blaze.

A fir, 15" dia., bears S.5¼°W., 25.2 ft., with a healed blaze.

Bury the original stone alongside the iron post.

Corner is located on a broken NE. slope, in a barbed-wire fence line, bears E. and W.

From this corner, the ¼ sec. cor. of sec. 9 only bears N.89°28'17"E., 208.22 ft., described on page 21963.

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 337500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 16 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of section 16 only, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "CAPE BLANCO CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:  
Latitude: 42°58'30.85"N.                      Longitude: 122°57'09.06"W.