

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 339100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 4 only, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - July 15, 1976 - M 56-49

-----  
Set 5/8" x 30" Iron rod and alum. cap.  
New BTs- 32" Fir S.8¼°W., 21.0 ft.  
5" Oak S.56½°W., 20.4 ft.

BLM dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group No. 2071, surveyed April/May 2004 - (DCSO records Vol. 55 Page(s) 21376)

-----  
The ¼ sec. cor. of sec. 4 only, on the N. bdy. of the Tp., established by Johnstone, in 1976, and is accepted as the cor., monumented with an iron rod, ¾" dia., firmly set, in a loose mound of stone, 2½ ft. base, 12" high, projecting 10" above the mound of stone, with aluminum cap mkd. 1/4 S4 ONLY, from which the remains of bearing trees mkd. by Johnstone  
A sawed fir stump, 29" dia., bears S.7¾°W., 19.9 ft., with no marks visible.  
A decayed oak stump, size indeterminate, bears S.59¾°W., 21.5 ft., with no marks visible.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with brass cap mkd

1/4 S 4  
T 31 S R 2 W  
2004

from which new bearing trees  
A fir, 5" dia., bears S.8½°E., 15.7 ft., mkd. ¼ S4 BT.  
A fir, 4" dia., bears S.74½°W., 43.8 ft., mkd. X BT.  
Deposit the iron rod inside and a magnet in a white plastic case at the base of the stainless steel post.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description