



PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group No. 2071, surveyed April/May 2004 - (DCSO records Vol. 55 Page(s) 21375-6)

-----  
The ¼ sec. cor. of sec. 33 only, T.30S., R.2W., perpetuated by Powell, in 1966, further perpetuated by Johnstone, in 1976, further perpetuated by Moffit, in 1986, monumented with an iron post, 1¼" dia., firmly set, in a mound of stone, 3 ft. base, 1½ ft. high, projecting 11 ins. above the mound of stone, with brass cap (properly) mkd.

from which the remains of original bearing trees

A sawed fir stump, 28" dia., bears South, 6.6 ft., with a healed blaze.

A cedar snag, 25" dia., bears N. 20° W., 11.9 ft., with scribe marks /4 S visible on a partially open blaze. and the remains of a bearing tree mkd. by Powell

A roothole, bears N.28¾°E., 26.1 ft., with the decayed hemlock trunk alongside, size indeterminate, with no marks visible.

and bearing trees mkd. by Moffit

A fir, 32" dia., bears N.30¾°E., 95.4 ft., with a healed blaze.

A fir, 20" dia., bears N.41½°W., 60.1 ft., with a healed blaze.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description