

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 9 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6830)

Set a basalt stone 16x10x6 ins., 11" in the ground for ¼ sec. cor. on S. bdy. sec. 9 marked ¼ on N. face, from which
A Fir 15" dia., bears N.32°E., 34 lks. dist. mkd. ¼ S9 BT.
A Fir 24" dia., bears N.84°W., 82 lks. dist. mkd. ¼ S9 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 11, 1968 - C.S. File 54/73-1

Found - No trace of corner stone called for.
Orig. 15" now 29" R.Fir, alive, N.32°E., 22.4 ft., open and find scribe.

NW. original BT turned out and lying face down.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 9
1968

New BT - 14" Cedar N.83°W., 18.4 ft. mkd. ¼ S9 CS BT.
Corner lies on moderate northerly slope.

Survey by Bruce A. Shaner, LS #430 - For: Longview Fibre Co. Aug. 1980 - RM 3-35

Found - Orig. 32" D.Fir, new uprooted stump, bears N.32°E., 22.4 ft.
Brass cap mkd. by the County in 1968.
15" Cedar bears N.83°W., 18.4 ft. with visible scribes.

New BT - 9" Cedar bears N.15°W., 31.7 ft. scribed ¼ S9 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2190, Surveyed June 2008 - (DCSO records Vol. 56 Page(s) 21966)

The ¼ sec. cor. of secs. 8 and 9, perpetuated by the Douglas County Surveyors Office in 1968, subsequently perpetuated by Shaner in 1981-82, further perpetuated by the Douglas County Surveyors Office in 1984, monumented with an iron post, 1¼" dia., firmly set, flush with ground surface, with brass cap (properly) mkd.

from which the remaining original bearing tree
A maple, 25" dia., bears S.53½°W., 4.3 ft., with no marks visible.

and the remains of a BT tree by Douglas County Surveyors Office in 1968 continued next page

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 9 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed, decayed fir stump, 13" dia., bears N.56¼°E., 53.6 ft., with no marks visible and a metal cover.
and bearing trees mkd. by Shaner
A fir, 38" dia., bears S.41°E., 48.7 ft., with a healed blaze.
A fir, 34" dia., bears S.78¾°W., 63.4 ft., with a healed blaze.
and BTs mkd. by Douglas County Surveyors Office in 1983
A fir, 34" dia., bears S.37¾°W., 14.1 ft., with a healed double blaze.
A maple, 16" dia., bears N.66½°W., 31.8 ft., with a healed blaze.
Corner is located on a N. slope, in a barbed-wire fence line, bears N. and S.
From the corner S.0°04'38"W., at:
145 ft. dist., dirt road, 9 ft. wide, bears N. 50° E. and S. 80° W., in curve.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22661)

The ¼ sec. cor. of sec. 9 only, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A roothole bears N.32°E., 22.4 ft., alongside of which is an uprooted, sawed, fir stump, 36" dia., with no marks visible.
A roothole bears N.84°W., 54.1 ft., alongside of which is a down fir snag, size indeterminate, with a healed blaze.
and a BT mkd. by the Douglas County Surveyors Office
A cedar, 26" dia., bears N.84½°W., 17.9 ft., with a healed blaze.
and a bearing tree mkd. by Shaner
A cedar, 11" dia., bears N.19°W., 32.0 ft., with a healed blaze.
Corner is located on a broken NE. slope in a barbed wire fence, bears E. and W.