

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 360200

PRIMARY CORNER DESCRIPTION E. 1/16 Cor. N. line Sec. 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Bruce A. Shaner - For: Umpqua National Forest -
Oct. 1967 - C.S. File 55/51 and RM 1-62

By proportional measurement, I set a monument from which a:
30" D.Fir scribed "E 1/16 S28 BT" bears N.66°E., 85.6 ft.
24" D.Fir scribed "E 1/16 S33 BT" bears S.79½°E., 79.4 ft

Jim Landrum-Leonard Herzstein, U.S. Forest Service - April 8,
1982 - C.S. File 61/32-9

Found - 1967 brass cap flush with and set in 6" dia.
concrete column, which projects 6" above ground,
properly marked. Set in 1967 by Shaner.

30" D.Fir snag, N.66°E., 85.6 ft. with scribe marks
"E 1/16 S28 BT" visible on partly healed blaze.
24" D.Fir S.79½°E., 80.6 ft. (Rec. 79.4 ft.) with
scribe marks "E S33 BT", visible on partly healed
blaze.

New BT - 4" madrone N.02½°W., 14.9 ft. scribed "E 1/16 S28
CS" on upper bark blaze and "BT" on lower axe
blaze.

New tie to existing Douglas County Road Dept. monument:
1½" alum. cap on 5/8" rebar firmly set, projecting
1" above ground with cap marked "R/W Douglas Co.
Rd. Dpt.", bears N.87°E., 47.7 ft. with guard
post mkd. "P.I. 28=78.29 100' R/W lt.", set 1 ft.
West.

Corner lies on steep SE. slope, 5 ft. West of old N-S fence
line; about 25 ft. West of 3 wire power line; and about 130
ft. NW. of County Rd. #46.