

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 379700

PRIMARY CORNER DESCRIPTION Sec Cor for 33 & 34 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6218)

Set a basalt stone 15x10x8 ins., 10" in the ground for cor. of secs. 33 and 34, marked 3 notches on E. and W. edges, from which

A Fir 14" dia., bears N.5°E., 105 lks. dist. mkd. T29S R2W S34 BT.

A Cedar 12" dia., bears N.30°30'W., 59 lks. dist. mkd. T29S R2W S33 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 14, 1968 - C.S. File 54/73-3

Found - Stone, approx. 15x10x8" at sec. corner. No notches seen.

12" now 18" Cedar N.30½°W., 38.9 ft., scribe visible

14" Fir now stump, N.5°E., 69.3 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R2W S 33 | S 34
T 30 S 1968 S 4

New BTs- 6" D.Fir N.24°E., 29.3 ft. mkd. T29S R2W S34 CS BT

7" D.Fir S.13°W., 11.7 ft. mkd. T30S R2W S4 CS BT.

This corner lies 26.8 ft. West of cor. to secs. 3 & 4 only, T30S-R2W.

Douglas Co. Surveyors Office - Crew: Stephen J Flauser & Jeff Lorsung - 9/30/2020 - C.S. File 67/46-44

Fd ok

Lat: 43.004762572 Long: -122.942078974