

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6753)

-----  
A Cedar 12" dia., for cor. secs. 3 & 4, 33 & 34, from which  
A Fir 36" dia., bears N.70°W., 15 lks.  
A Fir 15" dia., bears S.70°W., 12 lks.  
A Fir 15" dia., bears S.20°E., 11 lks.  
A Cedar 10" dia., bears N.89½°E., 73 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7686)

-----  
The sec. cor. which is nearly obliterated, one bearing tree gone, the other bearing tree and cor. deeply overgrown. I reestablish the cor. in its original position as follows:  
The original cor. A Cedar 16" dia., for cor. of secs. 3, 4, 33 and 34, I remark T30S S34 on NE.; R2W S3 on SE.; T31S S4 on SW.; S33 on NW. side with 3 notches on E. and W. sides, from which  
A Fir 10" dia., bears N.62°E., 83 lks. dist. mkd. T30S R2W S34 BT.  
A Fir 18" dia., bears S.20°E., 12 lks. dist. mkd. T31S R2W S3 BT.  
A Fir 18" dia., bears S.70°W., 13 lks. dist. mkd. T31S R2W S4 BT.  
A Fir 40" dia., bears N.70°W., 17 lks. dist. mkd. T30S R2W S33 BT.

Douglas Co. Surveyors Office - John M. Powell, & crew - Sept. 1966 - C.S. File 54/28-68

-----  
Found 15" Corner tree, scribe visible "T30S S33-34", from which  
10" D.Fir now 14", N.62°E., 54.0 ft., shows good scar.  
18" now 22" D.Fir, S.70°W., 8.6 ft., shows good scar.  
40" D.Fir N.70°W., 11.2 ft., scribe visible "T30S R1W S33"  
18" Fir, now stub, S.20°E., 7.9 ft.

Set Brass cap on South side of corner tree mkd:

County Surveyors Office  
T 30 S S 33 | S 34 R 2 W  
T 31 S S 4 | S 3  
1966

New BTs- 20" D.Fir S.10°E., 14.8 ft. mkd. T31S R2W S3 BT.  
8" Cedar N.35°W., 15.2 ft. mkd. T30S R2W S33 CS BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Glenn Baughman, PLS 536 - For: U.S. Forest Service  
- March 1978 - M 65-69

-----  
Found - 1966 DCSO brass cap.  
14" D.Fir bears N.62°E., 54.0 ft.  
24" D.Fir bears S.70°W., 8.6 ft.  
42" Fir bears N.70°W., 11.2 ft.  
18" D.Fir bears S.20°E., 7.9 ft., snag.  
20" D.Fir bears S.10°E., 14.8 ft.  
8" Cedar bears N.35°W., 15.2 ft., now down.  
15" Cedar corner tree.  
New BT - 12" D.Fir bears N.12°W., 33.4 ft. scribed T30S R2W  
S33 BT.

Survey by William Ruppert, LS #866 - For: U.S. Forest Service  
April 1979 - M 70-61

-----  
Found - 20" Cedar corner tree. A 1" Pipe with 2½" brass cap  
bears S.45°W., 1.3 ft. mkd. as per 1966.  
24" stump, very rotten, S.35°52'E., 8.0 ft.  
24" D.Fir, good face, S.6°22'E., 14.7 ft.  
20" D.Fir, good face, S.68°32'W., 7.3 ft.  
40" D.Fir, good face, N.66°35'W., 10.4 ft.  
10" D.Fir, good face, N.9°09'W., 32.6 ft.  
8" Cedar, windfall, N.36°09'W., 13.8 ft.  
New BT - 18" D.Fir N.62°00'E., 43.3 ft. scribed T30S R2W S34  
BT.

Gregory Lang - For: Phil Washburn, Roseburg Resources & Mark  
Hubbard - July 1994 - M 120-69

-----  
Found - Brass Cap  
17 3/4" Cedar Cor. Tree (turning snag)  
18" Fir, bears N.62°E., 43.3' (1979)  
21" Fir, bears S.68°32'W., 7.3'  
42" Fir, bears N.66°35'W., 10.4'  
Fir stump pile bears S.35°52'E., 8.0'  
24" Fir, bears S.6°22'E., 14.7'  
9" Cedar bears N.36°09'W., 13.8' (now down)  
12" Fir, bears N.9°09'W., 32.6'