

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6763)

-----  
Set ¼ sec. post and built stone mound, from which  
An Alder 18" dia., bears N.76°W., 83 lks.  
A Fir 12" dia., bears S.70°E., 107 lks.

Survey by Bruce A. Shaner - For: Umpqua National Forest - Oct. 1967 - C.S. File 55/51 and RM 1-62

-----  
By proportional measurement from the section corners immediately to North and South, I RE-SET the corner, which fell on bedrock on the South side of Elk Creek, on which rock I scribed an "X", from which a  
16" Cedar, I scribed "¼S S34 BT" bears N.65°E., 86.8 ft.  
10" D.Fir, I scribed "¼S S34 BT" bears N.16°E., 98.6 ft.  
10" D.Fir, I scribed "¼S S33 BT" bears N.53°W., 11.7 ft  
No original evidence found.

Survey by William Ruppert, LS #866 - For: U.S. Forest Service April 1979 - M 70-61

-----  
No monument found at corner. Corner relocated from bearing trees per Shaner 1967. Trees now bear  
18" D.Fir N.18°44'E., 98.5 ft., well healed.  
20" Cedar N.65°11'E., 86.9 ft., scribing visible.  
18" D.Fir N.51°51'W., 111.9 ft., well healed.  
Corner relocated by intersection of distances from bearing trees per C.S. File 55/51. Corner falls in Elk Creek.  
SET WIT. COR., a 2" x 30" galv. Iron pipe with 2½" brass cap in mound of stones, stamped "T30S R2W W.C. ¼ S33 S34 94.77' PLS 866 1979", from which new bearing trees:  
9" D.Fir N.64°15'W., 58.0 ft. "W.C. ¼ S33 BT"  
6" W.Fir S.13°39'E., 11.4 ft. "W.C. ¼ S34 BT"

Harold L. Center - For: Umpqua Nat'l Forest & Geoffrey Stark - Aug/Nov 1992 - M116-33 & C.S. File 63/151-1E

-----  
At the corner point I found an "X" carved in bedrock on the South bank of Elk Creek set by Bruce Shaner, P.E. 4906 in 1967, reference record survey number RM1-61, Douglas County Surveyor's Records. At the exact center of the carved "X" I cemented a 3-inch diameter brass disk marked  
T30S R2W  
1/4  
S33 + S34  
1992  
LS1071

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From which the following references

- An 18" dia. fir bears N.19°07'E., 98.80 ft. (Rec. N.16°E., 98.60 ft.) Healed blaze.
- A 20" dia. cedar bears N.65°23'E., 87.40 ft. (Rec N.65°E., 86.80 ft.) Healed blaze.
- A 14" dia. fir bears N.51°51'W., 111.70 ft. (Rec. N.53°W., 111.70 ft.) Healed blaze.
- A 2" dia. iron post with a 2½" dia. brass cap marked, "T3OS R2W, WC 1/4 PLS 866, 1979, 94.77." bears S.00°28'19"W., 94.70 ft. (Rec. S.00°10'17"W, 94.77 ft.)