

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6763)

-----  
Set post cor. secs. 27, 28, 33 and 34, from which  
An Oak 6" dia., bears N.10°E., 25 lks.  
A Fir 12" dia., bears S.20°E., 28 lks.  
A Laurel 10" dia., bears N.54°W., 21 lks.  
A Dogwood 6" dia., bears S.57°W., 23 lks.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson;  
Loren Weber - Aug. 2, 1940 - C.S. File 16/55

-----  
Location identified from original BT:  
A Fir 24" dia., S.20°E., 25 lks., scribe marks partly visible.  
Set a rock 8x8x20", 16" in ground marked X on top with 1 notch on S.; 3 notches on W.; 5 notches on N.; and 3 notches on E. corners, from which  
Fir 30" dia., bears S.53°W., 47.0 ft. mkd. T30S R2W S33 CS BT.  
Fir 36" dia., bears S.33°W., 42.2 ft. mkd. T30S R2W S34 CS BT.  
Fir 20" dia., bears N.43½°E., 29.1 ft. mkd. T30S R2W S27 CS BT.  
Fir 30" dia., bears N.37°W., 20.0 ft. mkd. T30S R2W S28 CS BT.

Survey by Bruce A. Shaner - For: Umpqua National Forest - Oct. 1967 - C.S. File 55/51 and RM 1-62

-----  
Found - 3/4" bolt beside 8x8x20" rock, from which a  
24" D.Fir BT bears S.20°E., 19.5 ft. to center.  
30" D.Fir BT now blown over and only a stump with an old face visible, bears S.53°W., 47.0 ft.  
20" D.Fir BT with bark scribes visible bears N.43½°E., 29.1 ft.  
Scribed- 30" D.Fir BT stump "S33 T30S R2W BT" bears S.5°W., 38.6 ft. to face.

Douglas Co. Surveyors Office - L.E. Monrean; M.L. Ladig, crew Dec. 31, 1975 - C.S. File 57/39-53

-----  
Found - 3x3x20" granite stone mkd. as recorded. Stone is dislodged with top X facing westerly. Stone dislodged by fallen tree. Found 3/4" bolt beside stone, loose.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Orig. Fir 12" now 30" dia., bears S.20°E., 18.5 ft.  
Tree has old blaze, I open and find orig.  
scribing "BT".  
A Fir 20" now 23" dia., bears N.42°E., 30.0 ft. to  
center, 29.1 ft. to face, (Rec. N.43½°E.) Tree is  
bark scribed "T30S R2W S27 BT".  
A Fir 30" now 31" dia., bears N.30°W., 22.5 ft. to  
center, 21.0 ft. to face. (Rec. N.37°W., 20.0  
ft.) Tree is bark scribed "T30S R2W S28 C".  
A Fir 30" dia., bears approx. S.53°W., 47.0 ft. Tree  
is uprooted, has old blaze.  
A Fir stump 30" dia., bears S.10°W., 38.6 ft. (Rec.  
S.5°W.). Stump is scribed "S33 T30S R2W BT".  
(Not of record). A rotted Fir stump approx. 15"  
dia., bears S.54½°W., 16.7 ft. Stump scribed "BT"  
No other bearing trees found.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 2 W  
S 28 | S 27  
S 33 | S 34  
1975  
Stone marked and bolt alongside cap. No new BTs scribed.

Survey by Loyd R. Moffit, LS #944 - For: U.S. Forest Service  
April 1985 - C.S. File 63/8-2

-----  
Found - 2½" brass cap on a 1" I.P. on South side of  
7"x8"x18" stone with "X" chiseled on top.  
30" Fir bears N.30°W., 22.2 ft., bark scribe visible  
24" Fir bears N.42°E., 30.2 ft., bark scribe visible  
30" Fir bears S.20°E., 18.4 ft., scribe visible.  
26" Fir stump bears S.10°W., 38.5 ft. scribe visible  
The remains of 12" Fir bears S.54½°W., 16.7 ft.  
scribe visible.  
New BT - A 6" Fir which bears S.33°W., 71.7 ft. mkd. T30S R2W  
S33 BT.