

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6764)

Set ¼ sec. post, from which
 An Oak 12" dia., bears S.12°W., 56 lks.
 An Oak 12" dia., bears S.30°E., 34 lks.

Ben B. Irving, D.C.S. - Wit: N.E. Richardson; Walter Leriwill; Vern Leriwill - Sept. 27, 1934 - C.S. File 37/176

Location identified from both original BTs as described original government field notes. Both trees have fallen down and decaying rapidly.
Set a 2½" x 18" Iron pipe for corner with a serpentine rock 6"x10"x18", alongside and mkd. ¼S on South face.
New BTs- 30" Pine, N.38°W., 32.5 ft. blazed ¼ S28 CS BT.
 Fir 30", N.40°40'E., 37.0 ft. blazed ¼ S28 CS BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-58

Found - 30" Pine, now stump, N.38°W., 32.5 ft.
 30" D.Fir, now stump, N.40½°E., 37.0 ft., bark scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office
 T 30 S R 2 W
 ¼ S 28 | S 27
 1968
New BTs- 14" D.Fir, West 10.5 ft. mkd. ¼ S28 CS BT.
 17" D.Fir N.63°E., 12.3 ft. mkd. ¼ S27 CS BT.