

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6764)

Set post cor. secs. 21, 22, 27 and 28, from which
An Oak 24" dia., bears S.5°E., 225 lks.
An Oak 10" dia., bears S.11°W., 210 lks.
An Oak 24" dia., bears N.16°E., 179 lks.
An Oak 18" dia., bears N.5°W., 115 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6800 and 6810)

(Page 6800)
The Sec. Cor., partially obliterated. No trace is found of the post. All the bearing trees are standing, deeply overgrown.
(Page 6810)
I re-establish the cor. of secs. 21, 22, 27 and 28, as follows:
Set a conglomerate stone 14x8x5 ins., 9½" in the ground for cor., marked with 2 notches on S. and 3 notches on E. edge, from which
A Yellow Pine 6" dia., bears N.71½°E., 79 lks. dist. mkd. T30S R2W S22 BT.
A Yellow Pine 8" dia., bears S.46½°E., 25 lks. dist. mkd. T30S R2W S27 BT.
A Yellow Pine 7" dia., bears S.51°W., 25 lks. dist. mkd. T30S R2W S28 BT.
An Oak 10" dia., bears N.44½°W., 20 lks. dist. mkd. T30S R2W S21 BT.

Survey by Bruce A. Shaner - Wit: James B. Griffin - For: National Plywood, Inc. - Aug. 5, 1060 - C.S. File 51/105-2

We found the stone established in the 1908 retracement survey, mkd. with 2 notches on the W. edge and 3 notches on the E. edge, 14x8x5 ins., 9½" in ground and from which a:
12" Ponderosa Pine, now blown down, but with scribes visible, bears N.71½°E., 79 lks. dist.
Ponderosa Pine root collar and chunk with scribes visible bears S.46½°E., 25 lks. dist.
Ponderosa Pine root collar and chunk with scribes visible bears S.51°W., 25 lks. dist.
16" Oak with faces visible, bears N.44½°W., 20 lks.
Left the original stone in place and from which a:
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" D.Fir bears N.70½°E., 46.9 ft. newly scribed T30S R2W S27 BT.
8" D.Fir bears S.64°E., 20.3 ft. new scribed T30S R2W S27 BT.
22" D.Fir bears S.55°W., 34.3 ft. newly scribed T30S R2W S28 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Dec. 1968 - C.S. File 54/73-52

Found - Stone firmly set at corner mkd. with grooves.
Orig. 16" B.Oak now 16", N.44½°W., 13.2 ft., shows good scar.
8" now 10" D.Fir S.64°E., 20.3 ft., shows good scars.
16" now 16" D.Fir N.70½°E., 46.9 ft., to face, pitched over scribe visible.
22" D.Fir S.55°W., 34.3 ft. to face, pitched over scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
S 21 | S 22
S 28 | S 27
1968

All bearing trees OK and tagged.

Fd. OK May 1990 by D. Bentz - M 110-16