

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6765)

Set ¼ sec. post, from which
A Fir 30" dia., bears S.75°W., 25 lks.
A Pine 24" dia., bears N.52°E., 29 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6799 and 6811)

(Page 6799)
The ¼ sec. cor. partially obliterated. No trace of the post is found and the SW. bearing tree is nearly dead.
(Page 6811)
I re-establish the ¼ sec. cor. as follows: (in its original position)
Set a conglomerate stone 14x8x6 ins., 9½" in the ground mkd. ¼ on W. face, from which
A Yellow Pine 28" dia., bears N.52°E., 31 lks. dist. mkd. ¼ S22 BT.
A Cedar 16" dia., bears N.51°W., 54 lks. dist. mkd. ¼ S21 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-20

Found - 16" now 23" Cedar N.51°W., 35.6 ft., shows good scar
28" Pine, now stump, N.52°E., 19.1 ft. (Rec. 20.5 ft.), burnt scribing visible and other marks.
Stone approx. size but with "+" on top instead of "¼".
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 21 | S 22
1968
New BT - 40" D.Fir S.80°E., 96.7 ft. mkd. ¼ S21 CS BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, Terrie Franssen, crew - Feb. 26, 1991 - C.S. File 64/13-7

Found - A 2½" dia. DCSO brass cap on a 1¼" O.D. Iron pipe, protruding 12" above ground.
Stone not visible on top of ground. We did not dig to look.
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" now 23" dia., 40 ft. high Cedar snag with a fully healed single blaze, bears N.51°W., 35.6 ft
28" now 20" dia. 2 ft. high Pine stump with rotted, open blazes, scribing visible "2", bears N.50°E., 19.1 ft. (Rec. N.52°E., 19.1 ft.)
40" now 42" dia. 4 ft. high D.Fir stump with a partially healed blaze, scribing visible "¼ S22 CS BT", bears S.81½°E., 96.7 ft. (Rec. S.80°E., 96.7 ft.)
New BTs- 7" dia. D.Fir, double blazed and scribed "¼ S22 CS BT", bears N.42°E., 31.7 ft.
9" dia. D.Fir, double blazed and scribed "¼ S22 CS BT" bears N.13°E., 20.1 ft.
10" dia. D.Fir, double blazed and scribed "¼ S21 CS BT" bears N.27°W., 31.3 ft.

Fd. OK, Oct. 1996 by K. DeGroot - M 125-80