

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6765)

Set post cor. secs. 15, 16, 21 and 22, from which
A Fir 36" dia., bears S.66°E., 118 lks.
A Fir 24" dia., bears N.2°E., 128 lks.
An Oak 12" dia., bears S.88°W., 300 lks.
A Laurel 18" dia., bears N.22°W., 252 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6799 and 6804-04)

(Page 6799)
The Sec. cor., is nearly obliterated. No trace is found of the post and the bearing trees are deeply overgrown.
(Pages 6804-05)
I re-establish the cor. in its original position as follows:
Set a porphyry stone 15x12x10 ins., 10" in the ground, for cor., mkd. with 3 notches on S. and E. edges, from which
A Fir 9" dia., bears N.41°E., 18 lks. dist. mkd. T30S R2W S15 BT.
A Yellow Pine 8" dia., bears S.50°E., 16 lks. dist. mkd. T30S R2W S22 BT.
A Fir 10" dia., bears S.54°W., 10 lks. dist., mkd. T30S R2W S21 BT.
A Madrone 8" dia., bears N.25°W., 37 lks. dist., mkd. T30S R2W S16 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - July 10, 1962 - C.S. File 42/421-21

Determined by O.B.T.s:
12" Laurel N.25°W., 24.4 ft., found scribe.
20" Fir, uproot, S.54°W., 6.6 ft.
22" Fir, uproot, N.41°E., 10.6 ft.
At corner point, found stone and SET 1½" x 30" I.P., from which
10" Cedar N.47°W., 7.8 ft. "S16 BT"
9" W.Fir bears North, 28.7 ft. "S15 BT"
5" Fir N.18°E., 21.0 ft. mkd. "SXXX BT"
15" Fir N.62°E., 42.0 ft. mkd. "SSS BT"

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13419-20)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The Sec. cor., monumented with a granite stone 14x10x9", firmly set 10" in the ground, mkd. with 3 grooves on N. face, and a cross X on top, from which the remaining original BTs:

A sawed Fir stump 50" dia., bears N.2°E., 128 lks. dist., mkd. with a well healed blaze.

A Fir 67" dia., bears S.66°E., 122 lks. dist., with no marks visible. (Rec. 118 lks.) Bark blaze and mark T30S R2W S22 BT.

A Madrone 48" dia., bears N.22°W., 252 lks. dist., mkd. with a completely healed blaze.

and trees mkd. by Mensch in 1909:

A fallen Fir 15" dia., bears N.41°E., 18 lks. dist., mkd. with a healed blaze.

A fallen Fir 15" dia., bears S.54°W., 10 lks. dist., mkd. with a healed blaze.

A Madrone 11" dia., bears N.25°W., 37 lks. dist., mkd. with a rotted and partially healed blaze.

and trees mkd. by Markham in 1959:

A Fir 8" dia., bears N.0¼°E., 43 lks. dist. mkd. S15 BT, on open blaze.

A Fir 5" dia., bears N.17¼°E., 31 lks. dist. mkd. XXX S BT, on open blaze.

A Fir 15" dia., bears N.62°E., 63 lks. dist., mkd. SSS BT, on open blaze. Reblazed and mkd. T30S R2W S15 BT.

A Cedar 9" dia., bears N.50½°W., 12 lks. dist. mkd. S16 BT, on open blaze. Reblazed and mkd. T30S R2W S16 BT.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 2 W	
S 16	S 15
S 21	S 22
1963	

from which a new bearing tree:

A Fir 13" dia., bears S.32¼°W., 151 lks. dist. mkd. T30S R2W S21 BT.

Deposit corner stone alongside the iron post.

Fd. OK, Feb. 1991 - M 111-49

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22655-6)

 The cor. of secs. 15, 16, 21, & 22, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, (alongside of which is a granite stone mkd. by Mensch, 14x10x9", loosely set, projecting 10 ins.cont.

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

..... above ground, with 3 grooves visible on N. face and a cross on top), with brass cap (properly) mkd.

from which the remains of the orig. bearing trees

A sawed fir stump, 48" dia., bears N.2°E., 84.5 ft., with a healed blaze.

A fir, 70" dia., bears S.66°E., 80.5 ft., with axe marks visible.

A madrone, 54" dia., bears N.22°W., 166.3 ft., with no marks visible on a hollow blaze.

and the remains of bearing trees mkd. by Mensch in 1909

A roothole bears N.41°E., 11.9 ft., alongside of which is a down, decayed, fir stump, 14" dia., with no marks visible.

A roothole bears S. 54° W., 6.6 ft.

and bearing trees mkd. by Markham, Jr., in 1962

A fir, 27" dia., bears N.0¼°E., 28.4 ft., with a healed blaze.

A fir, 22" dia., bears N.17¼°E., 20.5 ft., with no marks visible.

A fir, 22" dia., bears N.62°E., 41.6 ft., with a healed blaze.

A cedar, 29" dia., bears N.50½°W., 7.9 ft., with no marks visible.

and the remains of a bearing tree mkd. by White

A sawed fir stump, 31" dia., bears S.32¼°W., 99.7 ft., with a healed blaze.

and a new bearing tree

A fir, 5" dia., bears S.25¼°W., 38.2 ft., mkd. T30S R2W S21 BT.

Bury Mensch stone alongside the iron post.

Corner is located on nearly level ground, 2 ft. S.45°W. of a wood post at the cor. of barbed wire fences extending N., E., and W.