

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6843)

-----  
A Fir 28" dia. for ¼ sec. cor., I mark ¼ S9 on W. and 10 on E. side, from which  
    A Fir 12" dia., bears S.22½°E., 27 lks. dist. mkd. ¼ S10 BT.  
    A Fir 12" dia., bears N.47°W., 9 lks. dist. mkd. ¼ S9 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - Feb. 1960 - C.S. File 42/421-12

-----  
Determined by O.B.T.s:  
    16" W.Fir snag, S.22°E., 17.8 ft.  
    17" W.Fir snag, N.47°W., 6.0 ft.  
At corner point found 30" Fir snag scribed on West face and SET 3/4" x 30" Iron pipe, from which  
    9" Cedar N.33°E., 21.7 ft. mkd. ¼ S10 BT.  
    9" Cedar N.59°E., 27.0 ft. mkd. ¼ S10 BT.  
    9" W.Fir S.80°E., 24.0 ft. mkd. ¼ S10 BT.

Fd. OK, Oct. 23, 1968, DCSO, J.Powell - C.S. File 54/73

Tony Hostetter - For: Seneca Jones Timber Co. & Roseburg Resources Co. - April 2011 - M162-29

-----  
Found - 3/4" iron pipe by Markham (C.S. 42/421). from which:  
    9" Fir snag, scribing visible, N.33°E, 21.7 ft (Markham BT).  
    9" Fir snag, scribing visible, N.59°E., 27.0 ft (Markham BT).  
New BTs- 10" Cedar, scribed "S10 ¼ BT", S.37°E., 10.5 ft to spike.  
    14" Madrone, scribed "S9 ¼ BT" N.50°W., 10.3 ft to spike.