

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6199-6200) (Duplicate Pg. 6823-24)

-----  
A Fir 48" dia., for cor. of secs. 3, 4, 33 and 34, I mark T29S S34 on NE.; R2W S3 on SE.; T30S S4 on SW.; S33 on NW. sides, with 3 notches on E. and W. sides, from which  
A Cedar 12" dia., bears N.53°E., 136 lks. dist. mkd. T29S R2W S34 BT.  
A Fir 8" dia., bears S.35°E., 73 lks. dist. mkd. T30S R2W S3 BT.  
A Cedar 5" dia., bears S.89°W., 49 lks. dist. mkd. T30S R2W S4 BT.  
A Cedar 12" dia., bears N.54°W., 85 lks. dist. mkd. T29S R2W S33 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6217-6218)

-----  
Intersect the cor. of secs. 3, 4, 33 and 34, which is a Fir tree 48" dia. marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 3 and 4, T30S R2W only by destroying all marks referring to secs. 33 and 34. From cor.  
A Fir 8" dia., bears S.35°E., 73 lks. dist. mkd. T30S R2W S3 BT. (Old BT)  
A Cedar 5" dia., bears S.89°W., 49 lks. dist. mkd. T30S R2W S4 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct/Nov. 1968 - C.S. File 54/73-2

-----  
Found - Orig. 5" Cedar, now stob, S.89°W., 32.3 ft.  
No trace of SE. bearing tree.  
48" now 56" Corner tree, shows good scars.  
Set brass cap on S. side of corner tree, mkd. T29S R2W S34  
T30S 1968 S4 | S3  
New BTs- 6" Cedar S.82°E., 17.0 ft. mkd. T30S R2W S3 CS BT  
8" R.Fir S.64°W., 16.2 ft. mkd. T30S R2W S3 CS BT  
9" W.Fir N.80°E., 7.3 ft. mkd. T29S R2W S34 CS BT  
This corner lies 26.8 ft. East of Sec. cor. 33 & 34, T29-2