

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 438500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 15 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6829)

Set a conglomerate stone 15x12x8 ins., 10" in the ground, for 1/4 sec. cor. on N. bdy. Sec. 15, marked 1/4 on S. face, from which

A Madrone 8" dia., bears S.15 1/2°E., 45 lks. dist. mkd. 1/4 S15 BT.

A Fir 18" dia., bears S.40°W., 22 lks. dist., mkd. 1/4 S15 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-7

Found - 15x12x8 stone mkd. 1/4.
18" now 24" D.Fir, S.40°W., 14.5 ft., shows good scar.

8" now down, Laurel, S.15 1/2°E., 29.7 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 2 W

1/4

S 15

1968

New BT - 9" D.Fir S.10°W., 50.5 ft. mkd. 1/4 S15 CS BT.

Corner lies 8.0 ft. South of E-W fence line.