

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 439700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6217)

Set an Iron post 3 ft. long, 1" dia., 26" in the ground for ¼ sec. cor. of 34 only, with brass cap mkd. ¼ S34
1917

from which
A Fir 14" dia., bears N.18°15'E., 52 lks. dist. mkd. ¼ S34 BT.
A Fir 18" dia., bears N.72°30'W., 30 lks. dist. mkd. ¼ S34 BT.

Douglas Co. Surveyors Office - John Powell and crew - Nov. 26, 1968 - C.S. File 54/73-51

Found - GLO brass cap, properly mkd. in 1917.
14" now 26" D.Fir N.18°E., 34.3 ft., no scar visible
18" now 26" R.Fir N.72½°W., 19.8 ft., shows scar.
Reblazed and rescribed:
26" D.Fir N.18°E., 34.3 ft. mkd. "¼ S34 CS BT".